

QUOTATION

April 4, 2024

TO: AVAILABLE FOR PURCHASE

From: Phil Carrott

RE: Maintainer Service Body & Crane

Serial #: 240126 & 240127 Truck: 2024 Ford F600 Regular Cab 4x4, 6.7L Body Type: H7024ST-1-84

Quote #: Q13985-1

Service Body

Cost Variance Modifier (CVM), meaning that if high-inflation is incurred from our vendorssuppliers from the time of order to our unit build, we will have no choice but to requote prior to unit production; if multi-orders units are spread-out pricing could vary depending on timing.

Delivery of service body units and lube units (installed on chassis or ship-out body) are to be arranged by the selling dealer; Maintainer does not arrange shipping of complete units.

Chassis Disclaimer: All information and quote pricing shown with this proposal is based on a design utilizing the chassis make and model along with the specific features and options with the chassis as noted below. If any changes are made to the chassis type or options the proposal must be updated as they could change available unit features and options along with quote pricing. Any changes made without updating the quote will void this proposal.

Ex-factory delivery: 4th Quarter 2024

The body configuration below is based on these chassis' selections (Chassis is not included): Ford F600 4x4 TorqShift 10 Speed Automatic 84" CA Diesel (Regular Cab) Factory Options Selected: Diesel Motor, Factory Backup Camera, Rear Spring Suspension, Exhaust, Single Fuel Tank



Page 2 – Maintainer Service Body – Serial #: 240126 & 240127

Maintainer Body

Service Body - 1-Ton, 11ft x 52" Tall Compartments. 44" x 21" wheel well opening with skirting, front body bulkhead, body access grab handles, painted safety yellow (locations and number to vary with design).

52" tall galvannealed compartments with reinforced floors, clean out drains, 3/16" aluminum doors with automotive door seals, three-point D-ring door latches and gas spring door holders. 14 Gauge compartment tops and backs.

Factory installation of body on a chassis.

Additional Maintainer switches will be on a bracket/panel mounted in separate location.

Short Tower Crane reinforcement for MTS 1 ton service body (up to 45,100 ft*Lbs.)

Crane Location: Curb Side

Chassis Equipment & Accessories

Spring or spacer leveling package added to one side of chassis suspension (1-Ton)

Electronic engine speed control - computer set - electronic engine.

2.5 lb. ABC fire extinguisher and hazard reflectors.

Back-Up Alarm - 97 dB at 1 Meter

Camera, relocate existing chassis camera to rear of body

Note: Requires factory installed monitor

Fuel fill recessed into side rail

Hydraulic Power Package

Open Center Hydraulic Power Package with High Pressure Filter.

NOTE: The Open Center hydraulic system allows operation of only a single hydraulic component at a time. Multi-component operation requires a Closed Center system and is not available on some chassis configurations. Contact factory for details.

Open Center Hydraulic System Pump (Chelsea) Includes Pressure Reducer

Oil Reservoir - Complete, 28 Gallons (#028013) Composite. Tank only, excluding oil.

(28) Hydraulic Oil (Standard oil, per gallon) Oil good for -25° F startup and 9° F to 187° F operating temperature

No Reservoir Heater was Selected.

PTO for electric-over-hydraulic required on chassis with automatic transmission. (Ford F450-F550-F600, F650-F750 & Ram 4500-5500)



Page 3 – Maintainer Service Body - Serial #: 240126 & 240127

Welder / Generator / Inverter / Power Equipment

Mounting angles, 45" long. Includes mounting holes for common accessories.

Inverter-Light Duty-2000W Sensata CSW2012, Pure Sine Wave.

NOTE: Wired to chassis batteries. Customer to verify compatibility with electronic items.

Inverter mounted front of body, SS 1st vertical

Welder / Generator/ Inverter

Note: Inverter in SS1, mounted to rear side wall

Air Compressor Equipment & Accessories

VMAC H40 rotary screw hydraulic driven air compressor w/ black cover (Open Center).

40 CFM @ 150 PSI with integral hydraulic oil cooler. Includes control panel, mounted near body's switch panel & Hydraulic Soft Start.

Note: Hydraulic requirement = 14 GPM (May require large pump kit, not included). Cold weather package included (cooler bypass), additional oil warming valve available (open center only) (24"L x 16.5"W x 18"H) 162 Lbs.

Mounting angles for Air Compressor

Air tank - 17 gallon - Pressure Rating of 200 PSI with 16" diameter. Includes Moisture Drain, Painted Black.

Air accessory package - 1/2" X 50', spring rewind reel, hose & ball stop

1/2" Filter, Regulator, and Lubricator (FRL)

Fiber box; hose reel access. Limit 1 reel per fiber box.

Air Note: Air reel out SS rear

Outriggers & Accessories

Outriggers for cranes up to 45,100 Ft.*Lbs., hydraulic up/down rear outriggers (2) with hydraulic extend in/out on crane side (30" extend).

Outrigger pads, permanent (welded-on).

Compartment Equipment & Accessories

Pressurized Storage System (PSS), 2-blowers with filters

MasterLock System: Includes feet of Master Compartment Locking System for service body. Spring loaded with padlock guards for both side packs.



Page 4 – Maintainer Service Body - Serial #: 240126 & 240127

Street Side Vertical Compartment #1 - 52" Tall X 24" Wide X 23" Deep

12-Volt LED Strip Light

Door, Single, Vertical-hinged

- (2) Shelf, aluminum adjustable compartment shelf (250 Lbs. capacity) Installed
- 5+ Tool Storage Rack (027211) for (3x) M18 or D20 and (2x) M12 or D12 cordless power tools (each). Mounts to a compartment shelf (shelf not included)

Battery Storage Bracket (027057) for Milwaukee & Dewalt cordless power tool batteries.

Mounts to shelf channels. Fits (5) DeWalt 20v or (5) Milwaukee M18 batteries and (4) M12 Milwaukee batteries.

Street Side Vertical Compartment #2 - 52" Tall X 35" Wide X 23" Deep

12-Volt LED Strip Light

Door, Single, Vertical Hinged, Reverse Opening.

DuaLock or Bolt Bin - See configuration details and price below

Street Side Overwheel Compartment - 31" Tall X 44" Wide X 23" Deep

12-Volt LED Strip Light

Door, Double, Vertical-hinged

Shelf, aluminum adjustable compartment shelf (250 Lbs. capacity) - Installed

Street Side Rear Vertical Compartment - 52" Tall X 30" Wide X 23" Deep

12-Volt LED Strip Light

Door, Single, Vertical-hinged

DuaLock or Bolt Bin - See configuration details and price below

Curb Side Vertical Compartment #1 - 59" Tall X 24" Wide X 23" Deep

Above standard compartment height cost

Door, Single, Vertical-hinged

12-Volt LED Strip Light

2 Oxy/Act Bottle Storage Kit, contains ratchet strap, vents in door, (2) J-Hooks, reinforced floor (protective spray coated) and mounting side brackets.

Chain hanger bracket with no dividers. Contains upper and lower brackets. Protective spray coated.



Page 5 – Maintainer Service Body - Serial #: 240126 & 240127

Curb Side Vertical Compartment #2 - 52" Tall X 35" Wide X 23" Deep

12-Volt LED Strip Light

Door, Single, Vertical Hinged, Reverse Opening.

(2) Shelf, aluminum adjustable compartment shelf (250 Lbs. capacity) - Installed

Curb Side Overwheel Compartment - 31" Tall X 44" Wide X 23" Deep

12-Volt LED Strip Light

Door, Double, Vertical-hinged

DuaLock or Bolt Bin - See configuration details and price below

Curb Side Crane Pedestal - 47" Tall X 30" Wide X 23" Deep

12-Volt LED Strip Light

Door, Single, Vertical-hinged

Shelf, aluminum adjustable compartment shelf (250 Lbs. capacity) - Installed

Body switch panel located in this compartment.

Air compressor switch panel located in this compartment.

Lighting / Electrical Equipment & Accessories

Base Electrical Components - CAN System Includes Wiring Harnesses, Power Distribution Module, & Main Body Controller.

- 4.3" display CAN switch panel
- ~Grote FMVSS 108 LED Lighting/Reflector Kit: (2) Oval S/T/T/R, (2) Oval S/T/T,
 - (5) Red 3/4" Marker Lights, (2) Amber 3/4" Marker Lights.
- ~Strobe Lightheads, LED, oval, amber, recessed, 6.5" x 2.25" (pair).
- (6) Exterior 12V LED Flood Light 022232 (2,100 Lumens)

Paint, Undercoating, & Protective Spray Coating (PSC)

Unit Primed & Painted Urethane "White" color. Not a base coat/clear coat or Metallic Splatter Coating on interior of compartments
Undercoated

PSC- Level 30 •Compartment Fronts •Bottoms of Door Frames •Outside Area of Wheel Wells

- •Outer Vertical Outrigger Tubes •Bumper Sides & Step (Face & Top) •Bumper Top Surface
- •Bumper Vertical Surface •Center Deck Floor, Includes Welder Deck



Page 6 – Maintainer Service Body - Serial #: 240126 & 240127

•Cargo Side Walls, Includes Bulkhead •Compartment Tops, Includes Welded on Brackets/Guards.

Center Deck Equipment & Accessories

Center Deck Dimensions: 124" Long X 49" Wide X 1/8" Thickness

~1/8" Cargo floor (deck plate)

10" tall hinge-down "Slam Latch" aluminum tailgate (12" total Height, 10" tall above deck), protective spray front, paint on rear.

(6) Flush mount D-ring tie downs in bed floor (003217) each.

Rear Bumper & Accessories

26" steel workbench bumper with recessed step on curb side & 1 storage compartment.

Includes: Bolt-on yellow grab handles and strip light for recessed step safety.

~Bumper surface 3/16" smooth

~Transverse bar storage compartment in workbench bumper, flush to the floor.

Vise / grinder removable HD mounting plate, includes drain slots in plate.

Class IV hitch - 2" receiver - rated at 1,500 Lbs. vert. 10,000 Lbs. Includes safety chain loops MGTW. Note: customer is responsible to verify tow rating of chassis and available GVWR/GCWR remaining after loading of body and all other items.

Trailer plug-in 7-prong flat blade #007486 (RV style).

Miscellaneous Equipment & Accessories

Mud flaps, 1-ton, "Maintainer"

Parts and service manual (online & condensed paper version).

Maintainer Crane

H7024ST Crane 7,000 Lbs. max capacity (45,100 ft.*Lbs.) with hydraulic extend hex-boom 11'- 24'.

Note: Max capacity listed above is for 2-part line, for single-part line max capacity is 4,300 Lbs. Crane includes A2B, overload system and holding valves. ACC 2.1 (crane lifting weight display, capacity & speed limiting, stability monitoring and warn / stop feature).

Crane installed on body



Page 7 – Maintainer Service Body - Serial #: 240126 & 240127

No additional paint charge unless different color than body.

MIN GVW REQUIRED: 19,500.

Install hydraulic crane on body - includes boom saddle.

~Load Block (No Live Swivel) H6-H10

Planetary Winch (H6-H7) Ti1

Crane remote, wireless, push button (H6-H14) with true independent proportional control. Includes holder, hour meter and engine start/stop.

Backup cable for wireless crane remote, 35ft.

Annual crane inspection (initial inspection)

Paint Crane to match Service Body

Exterior 12V LED *flood lights on crane boom tip* (2-Lights, Ecco E92006, 1365 Lumens) on pivot bracket.

Umbrella mount on crane boom.

Street Side Vertical #2 Dualock - (7) drawer set #028096 (29" wide)

Housing Dimensions:41.5" Tall, 29" Wide, 18" Deep

Top Shelf is Standard, Drawers Listed from Top to Bottom

| Drawer # | Hei | ght Dividers |
|-----------|------|-------------------|
| Drawer 1 | 3" | Adjustable |
| Drawer 2 | 3" | Adjustable |
| Drawer 3 | 3" | Adjustable |
| Drawer 4 | 5" | Adjustable |
| Drawer 5 | 5" | Adjustable |
| Drawer 6 | 5" | Adjustable |
| Drawer 7 | 7" | Adjustable |
| BOTTOM SE | PACE | : 7.0 Inches Tall |



Page 8 – Maintainer Service Body - Serial #: 240126 & 240127

Street Side Rear Vertical Dualock - (5) drawer set #028097 (24" wide)

Housing Dimensions:30" Tall, 24" Wide, 18" Deep

Top Shelf is Standard, Drawers Listed from Top to Bottom

Drawer # **Height Dividers** 4" Drawer 1 Adjustable 4" Drawer 2 Adjustable 4" Drawer 3 Adjustable Adjustable Drawer 4 4" Drawer 5 4" Adjustable BOTTOM SPACE: 7.0 Inches Tall

Curb Side Over Wheel Bolt Bin - Custom Bolt Bin

Bolt Bin Layout: 2 Levels High, With 6 Bins Wide, 18" Deep Bins

Cabinet Dimensions:17.77" Tall, 35.5" Wide, 18.5" Deep

Top Shelf is Standard, with adjustable Wings

Qty of Bins: 12 Bin Height: 4.5" Bin Width: 5.25" Bin Depth: 18 Qty of Dividers: 36

BOTTOM SPACE: 4.5 Inches Tall

Non-Standard Sales Kits

• Remote mounted switch for inverter to be controlled at a separate location NOTE: Auxiliary switch mounted on dash for driver convenience to turn off / on



Page 9 – Maintainer Service Body - Serial #: 240126 & 240127

Maintainer Terms and Conditions

All prices are F.O.B. Sheldon, IA and in USD; Delivery of service and lube units are the dealer's responsibility. This quote does not include any applicable local, state or (F.E.T) federal taxes. Payment in full is required at time of order unless other terms are agreed upon prior to sale.

Ex-factory estimated delivery is July, 2024

Orders that are cancelled after booking will be subject to a \$500 cancellation processing fee, in addition to any restocking or costs for parts purchased for the cancelled unit. The fee will cover our incurred costs to process the order, plan production and released purchasing commitments. Orders are considered firm upon chassis confirmation, units are committed to a build slot, and serial numbers are assigned. Changes to booked orders are subject to change order fees. We have historically allowed flexibility on rearranging your builds order prior to week 10, if the swap is without changes to either spec. Units already released for production (weeks 8-10) will be reviewed on a case-by-case basis, but generally it is too late. It is possible they could be reassigned to the offline upfit department and you can get a quote for the changes.

Maintainer reserves the right to make changes and/or substitute components and product is subject to change without notice; Maintainer is not responsible for any Local, State, Federal or other regulations that maybe pertinent to quote/order.

The information contained in this quote, and all supporting documentation is confidential and may only be used by Maintainer, our dealer and/or the customer listed on this quote. We assume no liability for damage due to theft, vandalism, fire, weather, disaster, or damage due to gradual deterioration or inherent defect in such property.

We assume no liability for damage any kind during the storage of your chassis or parts on our premises while awaiting modification or installation. The storage location of the property shall be determined by Maintainer in its discretion. Exception to above is when directly attributable to our own gross negligence in moving or modifying chassis or parts, and in that event only to the extent of the wholesale used value of the chassis or parts as of the date of storage.